

Class I and Class II 500V ~ 3KV

中高壓溫度補償型及高誘電型陶瓷電容器



Unit:pF

	NPO	SL	B Y5E Y5P	E Z5U	F Z5V	DIAMTER MAX(mm)
500V	1~39	1~82	101~102	101~222	102~392	6
	47~56	91~161	122	242~332	472~502	7
	65~82		152~182	392~502	562	8
	90~101	181~301	202~222	562~682 103	682~103	9
			242~332	822		10
			362~472	153	153~223	11
			512~682			12
			752~103	203~333	333~473	15
1KV		47~68	101~501	101~222	102~182	6
		82~101	561~152	272~562	202~332	7
		151~221	182			8
			202~222	682~103	392~103	9
		271	272~332			10
		331	392~472		123	11
		391~471		153	153~183	13
		561~681	562~682	203~223	203~473	15
2KV			822~103			17
		10~56	101~561	102~122	102~222	6
		68~82	681~152	152~332	272~472	7
						8
				392~562	562~682	9
			182~332	682~103	822~103	10
			392~562			12
			682~822	153	153~203	15
3KV		5~47	101~471	102~182	102~182	6.5
	10~22	56~68	561~681	202~222	202~222	7.5
	25~33	82~101	821~122	272	272	8.5
	47~56		152	332~392	332~472	9.5
	68~101		182~222	472~562	562	10.5
					682	11.5
			272~332			12.5
			392~472	682~103	822~103	16
	According as customer's request and the voltage.					