

GA Series For General Purpose



項目 Item	特性 Characteristics																																											
使用溫度範圍 Operating Temperature Range	- 40 ~ 105°C	-25 ~ 105°C																																										
額定電壓範圍 Rated Working Voltage Range	10V ~ 100V DC	160V ~ 450V DC																																										
靜電容量容許差 Capacitance Tolerance (120Hz, 25°C)	±20% (M)																																											
洩漏電流 Leakage Current (25°C)	10V ~ 100V DC	160V ~ 450V DC																																										
	$I \leq 0.02CV + 3 (\mu A)$	$I \leq 0.03CV + 40 (\mu A)$																																										
I : Leakage Current (μA) C : Rated Capacitance (μF) V : Working Voltage (V) After 5 minutes applying the DC working Voltage																																												
突波電壓 Surge Voltage (25°C)	<table border="1"> <tr> <td>W.V.</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>100</td> <td>160</td> <td>200</td> <td>250</td> <td>350</td> <td>400</td> <td>450</td> </tr> <tr> <td>S.V.</td> <td>13</td> <td>20</td> <td>32</td> <td>44</td> <td>63</td> <td>79</td> <td>125</td> <td>200</td> <td>250</td> <td>300</td> <td>400</td> <td>450</td> <td>500</td> </tr> </table>		W.V.	10	16	25	35	50	63	100	160	200	250	350	400	450	S.V.	13	20	32	44	63	79	125	200	250	300	400	450	500														
W.V.	10	16	25	35	50	63	100	160	200	250	350	400	450																															
S.V.	13	20	32	44	63	79	125	200	250	300	400	450	500																															
散逸因素 (Tan. θ) Dissipation Factor (120Hz, 25°C)	<table border="1"> <tr> <td>W.V.</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>100</td> <td>160</td> <td>200</td> <td>250</td> <td>350</td> <td>400</td> <td>450</td> </tr> <tr> <td>Tan. θ</td> <td>0.20</td> <td>0.17</td> <td>0.15</td> <td>0.12</td> <td>0.10</td> <td>0.10</td> <td>0.20</td> <td>0.20</td> <td>0.20</td> <td>0.20</td> <td>0.20</td> <td>0.24</td> <td>0.24</td> </tr> </table> <p>For capacitance exceeding 1000 μF, add 0.02 per increment of 1000 μF</p>		W.V.	10	16	25	35	50	63	100	160	200	250	350	400	450	Tan. θ	0.20	0.17	0.15	0.12	0.10	0.10	0.20	0.20	0.20	0.20	0.20	0.24	0.24														
W.V.	10	16	25	35	50	63	100	160	200	250	350	400	450																															
Tan. θ	0.20	0.17	0.15	0.12	0.10	0.10	0.20	0.20	0.20	0.20	0.20	0.24	0.24																															
溫度特性 Temperature Characteristics	<table border="1"> <tr> <td>W.V.</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td>100</td> <td>160</td> <td>200</td> <td>250</td> <td>350</td> <td>400</td> <td>450</td> </tr> <tr> <td>-25°C / +25°C</td> <td>4</td> <td>3</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>8</td> <td>8</td> <td>8</td> <td>12</td> <td>16</td> <td>16</td> </tr> <tr> <td>-40°C / +25</td> <td>8</td> <td>6</td> <td>4</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> <td>6</td> <td>8</td> <td>10</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table> <p>Impedance ratio at 120HZ</p>		W.V.	10	16	25	35	50	63	100	160	200	250	350	400	450	-25°C / +25°C	4	3	3	2	2	2	2	8	8	8	12	16	16	-40°C / +25	8	6	4	3	3	3	3	6	8	10	-	-	-
W.V.	10	16	25	35	50	63	100	160	200	250	350	400	450																															
-25°C / +25°C	4	3	3	2	2	2	2	8	8	8	12	16	16																															
-40°C / +25	8	6	4	3	3	3	3	6	8	10	-	-	-																															
高溫負荷特性 Load Test	<p>After 2000 hours application of W.V. at +105°C the capacitor shall meet he following limits</p> <table border="1"> <tr> <td>Capacitance change</td> <td>$\leq \pm 20\%$ of initial value</td> </tr> <tr> <td>Tan. θ</td> <td>$\leq \pm 150\%$ of initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>\leq initial specified value</td> </tr> </table>		Capacitance change	$\leq \pm 20\%$ of initial value	Tan. θ	$\leq \pm 150\%$ of initial specified value	Leakage current	\leq initial specified value																																				
Capacitance change	$\leq \pm 20\%$ of initial value																																											
Tan. θ	$\leq \pm 150\%$ of initial specified value																																											
Leakage current	\leq initial specified value																																											
放置特性 Shelf Test	<p>After 500 hours application of W.V. at +105°C the capacitor shall meet he following limits</p> <table border="1"> <tr> <td>Capacitance change</td> <td>$\leq \pm 20\%$ of initial value</td> </tr> <tr> <td>Tan. θ</td> <td>$\leq 200\%$ of initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>$\leq 200\%$ of initial specified value</td> </tr> </table>		Capacitance change	$\leq \pm 20\%$ of initial value	Tan. θ	$\leq 200\%$ of initial specified value	Leakage current	$\leq 200\%$ of initial specified value																																				
Capacitance change	$\leq \pm 20\%$ of initial value																																											
Tan. θ	$\leq 200\%$ of initial specified value																																											
Leakage current	$\leq 200\%$ of initial specified value																																											

