

SL 系列低漏電品
Series Low Leakage Current




項目 Item	特性 Characteristics																					
使用溫度範圍 Operating Temperature Range	- 40 ~ 105°C																					
額定電壓範圍 Rated Working Voltage Range	6.3V ~ 50V DC																					
靜電容量容許差 Capacitance Tolerance (120Hz, 25°C)	±20% (M)																					
洩漏電流 Leakage Current (25°C)	$I \leq 0.02CV + 0.4 (\mu A)$ I : Leakage Current (μA) C : Rated Capacitance (μF) V : Working Voltage (V) After 5 minutes applying the DC working Voltage																					
突波電壓 Surge Voltage (25°C)	<table border="1"> <tr> <td>W.V.</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <td>S.V.</td> <td>8</td> <td>13</td> <td>20</td> <td>32</td> <td>44</td> <td>63</td> </tr> </table>	W.V.	6.3	10	16	25	35	50	S.V.	8	13	20	32	44	63							
W.V.	6.3	10	16	25	35	50																
S.V.	8	13	20	32	44	63																
散逸因素 (Tan. θ) Dissipation Factor (120Hz, 25°C)	<table border="1"> <tr> <td>W.V.</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <td>Tan. θ</td> <td>0.25</td> <td>0.20</td> <td>0.17</td> <td>0.15</td> <td>0.12</td> <td>0.10</td> </tr> </table>	W.V.	6.3	10	16	25	35	50	Tan. θ	0.25	0.20	0.17	0.15	0.12	0.10							
W.V.	6.3	10	16	25	35	50																
Tan. θ	0.25	0.20	0.17	0.15	0.12	0.10																
溫度特性 Temperature Characteristics	<table border="1"> <tr> <td>W.V.</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> </tr> <tr> <td>-25°C /+25°C</td> <td>6</td> <td>4</td> <td>3</td> <td>3</td> <td>2</td> <td>2</td> </tr> <tr> <td>-40°C /+25</td> <td>10</td> <td>8</td> <td>6</td> <td>4</td> <td>3</td> <td>3</td> </tr> </table> <p>Impedance ratio at 120HZ</p>	W.V.	6.3	10	16	25	35	50	-25°C /+25°C	6	4	3	3	2	2	-40°C /+25	10	8	6	4	3	3
W.V.	6.3	10	16	25	35	50																
-25°C /+25°C	6	4	3	3	2	2																
-40°C /+25	10	8	6	4	3	3																
高溫負荷特性 Load Test	<p>After 2000 hours application of W.V. at +105°C the capacitor shall meet he following limits</p> <table border="1"> <tr> <td>Capacitance change</td> <td>$\leq \pm 20\%$ of initial value</td> </tr> <tr> <td>Tan. θ</td> <td>$\leq \pm 200\%$ of initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>\leq initial specified value</td> </tr> </table>	Capacitance change	$\leq \pm 20\%$ of initial value	Tan. θ	$\leq \pm 200\%$ of initial specified value	Leakage current	\leq initial specified value															
Capacitance change	$\leq \pm 20\%$ of initial value																					
Tan. θ	$\leq \pm 200\%$ of initial specified value																					
Leakage current	\leq initial specified value																					
放置特性 Shelf Test	<p>After 500 hours application of W.V. at +105°C the capacitor shall meet he following limits</p> <table border="1"> <tr> <td>Capacitance change</td> <td>$\leq \pm 20\%$ of initial value</td> </tr> <tr> <td>Tan. θ</td> <td>$\leq 200\%$ of initial specified value</td> </tr> <tr> <td>Leakage current</td> <td>$\leq 200\%$ of initial specified value</td> </tr> </table>	Capacitance change	$\leq \pm 20\%$ of initial value	Tan. θ	$\leq 200\%$ of initial specified value	Leakage current	$\leq 200\%$ of initial specified value															
Capacitance change	$\leq \pm 20\%$ of initial value																					
Tan. θ	$\leq 200\%$ of initial specified value																					
Leakage current	$\leq 200\%$ of initial specified value																					

SL

尺寸圖

Dimension

A



D	5	6	8	10
$F \pm 0.5$	2	2.5	3.5	5
$d \pm 0.02$	0.5	0.5	0.5	0.6

μF	WV	D x L (m/m)								
		10	16	25	35	50				
0.1									5*11	1
0.22		尺寸 Dimension : $\phi D \times L$ (mm)							5*11	4
0.33		紋波電流 Ripple Current : mA (rms) at 120Hz 105°C							5*11	4
0.47									5*11	6
1									5*11	17
2.2									5*11	29
3.3									5*11	34
4.7									5*11	43
10				5*11	60	5*11	67	6*11	78	
22			5*11	67	5*11	80	5*11	92	6*12	121
33	5*11	65	5*11	90	5*11	97	6*11	132	8*12	148
47	5*11	74	5*11	116	6*11	134	8*12	158	8*12	206
100	6*11	170	6*12	241	8*12	263	8*14	295	10*17	371
220	8*12	281	8*12	309						